
Outline of the Rokkasho MOX Fuel Fabrication Plant



Japan Nuclear Fuel Ltd.


JNFL Business and JMOX Roll





Scope of JMOX Business





JMOX business: To fabricate MOX fuel (both for BWR and PWR) feeding MOX powder recovered at RRP and UO2 powder for dilution, through to ship them to domestic nuclear power plants.

Policy on Transplanting MOX Fabrication Technology




JMOX project is promoted on a policy that it should stand on technologies widely proven domestically and abroad.

| Field of technology | Contents of technology | Character of technology | Who's technology |
|------------------------------------|---|--|---|
| Safe handling of Pu | Confinement, Radiation shielding, Criticality prevention, Safe operation with gloves | Basic technology to operate the MOX business | JAEA |
| Accountability /Safeguards | To prove that SNM is limited for peaceful use | Inevitable technology to achieve MOX business in Japan | JAEA |
| MOX fuel fabrication for LWR | Technology for equipment selection and plant operation to produce high quality MOX fuel | To achieve commercial scale production | JAEA Domestic U fabricator Foreign MOX fabricator |

MOX Fuel Fabrication Process Flow





Feed MOX Powder to JMOX (MH-MOX)




- MH-MOX means MOX powder converted by <u>Microwave</u>
 <u>Heating Direct De-nitration method.</u>
- MH technology, applied in RRP, is the ways in which U and Pu mixed solution is converted into mixed oxide having merits that the way is simple and powder has good character, although waste to be generated is rather small.
- JAEA developed the MH method because of world requirement on nuclear nonproliferation.

Powder Dosing Process (MIMAS technology)



- JNFL decided applying MIMAS technology that contributes great deal to MELOX's good running in JMOX key process.
- MIMAS technology is two steps powder mixing technology. In the 1st step, so called "master powder" having 30% of plutonium content is dosed and milled well, then, at the 2nd step, UO2 powder is put to the master powder to dilute the plutonium content defined as vender specification.



- MIMAS (<u>Mi</u>cronized <u>Mas</u>ter Blend)
- Because feed powder to JMOX is Japanese typical MH-MOX, JNFL needs developing confirmation that MIMAS harmonizes with MH-MOX.

Safety Measures



 To proceed fully with safety measures considering MOX fuel characteristics and safety regulations domestic and abroad.

Release control of radioactive waste

Confinement
(Measures for inner exposure)

Radiation shielding (Measures for outer exposure)

Measures against missiles

Safety measures of JMOX

Measures for criticality safety


Measures against fire and explosion

Measures against earthquake

Measures for removal of heat by disintegration

Confinement (to prevent contamination spreading by pressure control)






Radiation Shielding



- To prevent radiation to public:
 - To handle SNM in basement
 - Building wall effect to shield radiation
- To prevent radiation to operators:
 - Automated operation and/or remote operation
 - Shielding of equipment itself (Glovebox and machine)



Philosophy of Criticality Safety Measures




Dry process



Not to put water to MOX powder nor make mixture of MOX powder and water in fabrication process.


Mass control




To handle with MOX powder less than Nuclear Material Limits that is far smaller than criticality mass.

Configuration control

Neutron absorption control



To maintain certain distance between each of MOX powder.



To use neutron absorber properly.

Heat Removal Measures



 Evacuating by ventilation system enough air necessary to remove heat generated by disintegration.

Glovebox Fuel assemblies storage To exhaust To exhaust High efficiency Air air filter Fuel assembly Heat Air **High efficiency** air filter

Measures against Earthquake



 Putting enough strength to building and equipment in order to withstand an assumed earthquake scale.

Measures against Fire and Explosion

- Using nonflammable and fire-resistive material.
- Nitrogen atmosphere in main glovebox
- Glovebox to be equipped with fire detection, alarm and self firefighting system
- Building to be equipped with fire detection, alarm and fire-fighting system


Measures against Missiles

 Ensuring the outer wall of the building with enough strength against crash of airplane in maneuvers

Release Control of Radioactive Gaseous Waste

te


To filter the gaseous waste from the plant by high efficiency air filter and control releasing monitoring that the density of radioactive materials is under the legal limits.



Release Control of Radioactive Liquid waste




To filter the liquid waste from the plant by filtration system and control releasing monitoring that the density of radioactive materials is under the legal limits.



Impact on Environment by Accidents or Troubles


In case that MOX powder spreads in process room by mal-operation, disorder/fire/explosion of equipment radiation dose to public can be lowered enough under 0.01mSv at maximum.



Case Study on Hypothetical Criticality Accident



- JNSC requests any MOX facilities to evaluate case study on hypothetical criticality accidents.
- Upon the requirement, an evaluation based that 5 x 10¹⁸ fissions had happened at equipment that treats with largest MOX powder shows radiation dose to public at the facility border is less than 5 mSv.
- The evaluated dose lies far below 2 5 0 mSv, standards shown in the JNSC guideline.



Outline of MOX Fuel Fabrication Plant



Maximum throughput: 130t-HM/y

Output: Fuel assembly to be shipped out to domestic

nuclear power plants (both PWR and BWR)

Scale of main building: 80mX80m, 3 basement floors, 2 stories,

reinforced concrete

JMOX siting plan: To become adjacent to RRP

Investment: Approximately 1 b\$

Prospective operators: 300



Construction Program



